

ALLOY DATA SHEET



G30CrMo4

Visit our website
www.safe-metal.com



WHO ARE WE ?

Safe Metal is the world leader in steel components made by green sand casting. Our teams operate as part of an international network that stretches across Europe, America and Asia, and partner their sales and project management skills with those of their customers.

MAKING WORLD CLASS

Thanks to the expert skills of our R&D department, we are able to improve our industry knowledge and hence our products, our production process and metalworking by choosing the most appropriate methods for the product



G30CrMo4

Generality

High carbon steel chromium-molybdenum for high mechanical characteristics at treated condition. Good hardenability and low weldability.

Market : this alloy can be used in all markets.



Chemical Composition

C (%)	Si (%)	Mn (%)	P (%)	S (%)	Cr (%)	Mo (%)
0,27 – 0,33	< 0,4	0,6 – 0,9	< 0,035	< 0,035	0,90 – 1,2	0,15 – 0,25

Main characteristics

G30CrMo4

Family : High resistance

Weldability



Impact test values



Machining



Cost



Mechanical resistance



G30CrMo4


Mechanical characteristics & Heat treatment

Designation			Heat Treatment		Thickness	Mechanical properties					
Reference	Name	Number	Symbol	Normalizing or austenitizing °C		Tempering °C	t mm	Tensile test at room temperature			Impact test
					R _{p0.2} MPa min.			R _m Mpa min.	A% min.	KV J min.	Temp. °C
Safe Metal possibilities according to norms :											
	G30CrMo4	Not in EN 10293:2015 standard – Closer alloys : G26CrMo4 (1.7221) or G34CrMo4 (1.7230)									
Safe Metal other possibilities :											
Safe Metal	G30CrMo4		+N			t ≤ 30	590	840	8	5	-20
Safe Metal	G30CrMo4		+QT HR		High Rm	t ≤ 30	800 to 940	900 to 1040	8	16	-20
Safe Metal	G30CrMo4		+QT M		Balanced Rm/Kv	t ≤ 30	660 to 800	780 to 900	13	47	-20
Safe Metal	G30CrMo4		+QT HD		High Kv	t ≤ 30	530 to 660	650 to 780	17	80	-20


RT : Room temperature HR : High resistance N : Normalized
 QT : Liquid quenched and tempered HD : High ductility

Microstructures


QUENCHING + TEMPERED AT 500 °C



QUENCHING + TEMPERED AT 600 °C



NORMALIZED



Machining

			HB*	Microstructure
Safe Metal	G30CrMo4	N	245	Ferrite + Pearlite + Bainite
Safe Metal	G30CrMo4	QT HR	335	Tempered Martensite
Safe Metal	G30CrMo4	QT M	245	Tempered Martensite
Safe Metal	G30CrMo4	QT HD	190	Tempered Martensite


HB : Brinell hardness

G30CrMo4

Welding

Preheating conditions according to thickness and equivalent carbon. A specific zone is defined where preheating is not absolutely necessary and depends on the case.

G30CrMo4



Welding comparative table

Grade	Group (ISO TR 15608)	Filler Metal	Post-Welding HT	Hardness of melted area (Hv10)	Rm (MPa)	Process (acc. NFEN ISO 15614)
C steel						
C25	1.2	E71T6	SR/N	130-170	450-550	
		E71T6	QT	150-200	550-550	
G20Mn5	1.2	E70C6 M H4	SR/N	150-200	500-550	
		E70C6 M H4	QT	160-220	540-580	
G24Mn5	3.1	ER110T5	SR	240-300	750-800	
		ER110T5	QT	260-340	780-860	
G28Mn6	3.1	ER80S02	SD			
G30MnV5	3.1	ER80S02	SD			
GE230	1.1	E71T5	SR/N	130-170	450-550	
		E71T5	QT	150-200	550-550	
GE280	1.2	E70C6 M H4	SR/N	150-200	500-550	
		E70C6 M H4	QT	160-220	540-580	
G20MnV5	3.1	ER110T5	SR	240-300	750-800	
		ER110T5	QT	260-340	780-860	
Cr-Mn						
G18CrMo4	5.1	E9018B3	SR	180-250	620-660	111/135
G25CrMo4	5.1	E9018G	QT	200-260	630-720	111/135
G30CrMo4	5.1	E12018G	QT	300-350	950-1150	111
G21CrMoV5-11	6.2	E13018G	SR	280-350	800-1000	111
Others						
G10MnMoV5	3.1	ER80 S-G	SR	200-280	620-660	
		ER80 S-G	QT	160-220	580-640	
G20NiCrMo4	4.2	ER120 S-G	SR	300-350	900-950	
		ER120 S-G	QT	280-350	920-1020	

111 : Electrode welding
135 : MIG


SR : Stress relieving
QT : Quenched and Tempered

N : Normalized

G30CrMo4

Comparative Table of Safe Metal grades

Chemical composition										N			QT (Q235°C)		
C-Mn	C (%)	Mn (%)	Si (%)	Cr (%)	Mo (%)	V (%)	Ni (%)	Co (%)	Fe (%)	Rm	AN	Kv (-20°C)	Rm	AN	Kv (-20°C)
C25	0,2	0,7	0,53					0,32	440	23	22	420-520	20-25	40-50	
GE240	0,23	0,9	0,5					0,4	480	25	12	570-600	25-30	oct-20	
GE280	0,24	1,2	0,5	0,15				0,47	530	20	10	600-800	15-25	20-40	
G20Mn5 (low)	0,2	1,1	0,4					0,38	470	28	40	500-590	20-22	38-46	
G20Mn5 (high)	0,23	1,4	0,5					0,5				600-880	dec-25	25-30	
G20MnV6	0,23	1,55	0,5			0,05		0,54	580	25	10				
G24Mn6 (low)	0,23	1,05	0,5					0,52	590	18	10	550-670	20-25	40-75	
G24Mn6 (high)	0,25	1,8	0,5					0,6	630	32	10	620-900	oct-18	15-35	
G28Mn6	0,3	1,4	0,5					0,53	650	17	10	650-840	oct-15	30-60	
G30MnV6	0,3	1,4	0,5					0,55	650	12	80	700-930	dec-dec	80-45	
Chemical composition										N			QT (Q235°C)		
Cr-Mo	C (%)	Mn (%)	Si (%)	Cr (%)	Mo (%)	V (%)	Ni (%)	Co (%)	Fe (%)	Rm	AN	Kv (-20°C)	Rm	AN	Kv (-20°C)
G18CrMo4	0,18	0,8	0,4	1	0,2			0,55	450	18	10	580-720	dec-22	30-80	
G25CrMo4	0,25	0,8	0,4	1	0,2			0,62	660	11	12	600-950	oct-18	20-90	
G30CrMo4	0,3	0,8	0,4	1	0,2			0,67	840	5	10	650-1050	oct-18	20-90	
G31CrMoV5-11	0,2	0,7	0,5	1,15	1	0,3		0,82	980	5	5	900-1200	oct-ect	5	
Chemical composition										N			QT (Q235°C)		
Others	C (%)	Mn (%)	Si (%)	Cr (%)	Mo (%)	V (%)	Ni (%)	Co (%)	Fe (%)	Rm	AN	Kv (-20°C)	Rm	AN	Kv (-20°C)
G10MnMoV6	0,12	1,55	0,5		0,3	0,08		0,43	460	17	10	580-750	14-16	20-50	
G20NiMoCr4	0,18	1	0,4	0,4	0,6		0,3	0,62	750	5	10	600-950	dec-20	35-100	



Family : Versatile



Family : Versatile

A circular micrograph showing a single cell. The cell has a large, dark, irregularly shaped nucleus containing a smaller, lighter-colored nucleolus. The cytoplasm is filled with various organelles and granules, appearing as a textured, light gray area surrounding the nucleus.

© 2000 Blackwell Science Ltd



Family: Muscivora

Family: Versatile



CONCLUSIONS



Family: Versatile



Family : Versatile



Family : High resistance

Family : High resistance

Family : High resistance

Family : High resistance



Family : Special



Family : Special



Family : Cast iron

